

## Features

- Low profile provides compatibility with DIPs
- Compatible with automatic insertion equipment
- Superior package integrity
- Marking on contrasting background for permanent identification

- Top marking standard

# 4300R Series - Thick Film Molded SIPs

## Product Characteristics

Resistance Range .....10 ohms to 10 megohms  
 Maximum Operating Voltage.....100V  
 Temperature Coefficient of Resistance  
 50Ω to 2.2 MΩ.....±100ppm/°C  
 below 50Ω.....±250ppm/°C  
 above 2.2 MΩ.....±250ppm/°C  
 TCR Tracking .....50ppm/°C  
 maximum; equal values  
 Resistor Tolerance .....See circuits  
 Operating Temperature  
 .....-55°C to +125°C  
 Power Rating .....Derate to zero  
 power from +70°C to +125°C  
 Insulation Resistance  
 .....10,000 megohms minimum  
 Dielectric Withstanding Voltage  
 .....200 VRMS  
 Lead Solderability  
 .....Meet requirements of MIL-STD-202  
 Method 208

## Environmental Characteristics


TESTS PER MIL-STD-202.....ΔR MAX.  
 Short Time Overload.....±0.25%  
 Load Life.....±1.00%  
 Moisture Resistance.....±0.50%  
 Resistance to Soldering Heat  
 .....±0.25%  
 Terminal Strength.....±0.25%  
 Thermal Shock.....±0.25%

## Physical Characteristics

Flammability .....Conforms to UL94V-0  
 Lead Frame Material  
 .....Copper, solder coated  
 Body Material .....Novolac epoxy


## How To Order

**43 06 R - 101 - 222**



Consult factory for other available options.

## Package Power Temp. Derating Curve




## Package Power Rating at 70°C


4306R	0.75 watts
4308R	1.00 watts
4309R	1.13 watts
4310R	1.25 watts
4311R	1.38 watts

## Typical Part Marking

Represents total content. Layout may vary.



## Product Dimensions



Governing dimensions are in metric. Dimensions in parentheses are inches and are approximate.


\*Terminal centerline to centerline measurements made at point of emergence of the lead from the body.

# 4300R Series - Thick Film Molded SIPs



## Isolated Resistors (102 Circuit)

Model 4306R-102-RC (6 Pin)  
 Model 4308R-102-RC (8 Pin)  
 Model 4310R-102-RC (10 Pin)



These models incorporate 3, 4 or 5 isolated thick-film resistors of equal value, each connected between two pins.


### Resistance Tolerance

10 ohms to 49 ohms .....±1 ohm  
 50 ohms to 5 megohms.....±2%\*  
 Above 5 megohms.....±5%

### Power Rating per Resistor


At 70°C .....0.30 watt

### Power Temperature Derating Curve



## Bussed Resistors (101 Circuit)

Model 4306R-101-RC (6 Pin)  
 Model 4308R-101-RC (8 Pin)  
 Model 4309R-101-RC (9 Pin)  
 Model 4310R-101-RC (10 Pin)  
 Model 4311R-101-RC (11 Pin)



These models incorporate 5, 7, 8, 9 or 10 thick-film resistors of equal value, each connected between a separate pin.


### Resistance Tolerance

10 ohms to 49 ohms .....±1 ohm  
 50 ohms to 5 megohms.....±2%\*  
 Above 5 megohms.....±5%

### Power Rating per Resistor


At 70°C .....0.20 watt

### Power Temperature Derating Curve



## Dual Terminator (104 Circuit)

Model 4306R-104-R1/R2  
 Model 4308R-104-R1/R2 (shown)  
 Model 4309R-104-R1/R2  
 Model 4310R-104-R1/R2  
 Model 4311R-104-R1/R2



4308R-104 (shown above) is an 8-pin configuration and terminates 6 lines. Pins 1 and 8 are common for ground and power, respectively. Twelve thick-film resistors are paired in series between the common lines (pins 1 and 8).


### Resistance Tolerance

Below 100 ohms.....±2 ohms  
 100 ohms to 5 megohms.....±2%\*  
 Above 5 megohms.....±5%

### Power Rating per Resistor

At 70°C .....0.20 watt

### Power Temperature Derating Curve



## Popular Resistance Values (101, 102 Circuits)\*\*

Ohms	Code	Ohms	Code	Ohms	Code	Ohms	Code	Ohms	Code
10	100	180	181	1,800	182	15,000	153	120,000	124
22	220	220	221	2,000	202	18,000	183	150,000	154
27	270	270	271	2,200	222	20,000	203	180,000	184
33	330	330	331	2,700	272	22,000	223	220,000	224
39	390	390	391	3,300	332	27,000	273	270,000	274
47	470	470	471	3,900	392	33,000	333	330,000	334
56	560	560	561	4,700	472	39,000	393	390,000	394
68	680	680	681	5,600	562	47,000	473	470,000	474
82	820	820	821	6,800	682	56,000	563	560,000	564
100	101	1,000	102	8,200	822	68,000	683	680,000	684
120	121	1,200	122	10,000	103	82,000	823	820,000	824
150	151	1,500	152	12,000	123	100,000	104	1,000,000	105

\* ±1% TOLERANCE IS AVAILABLE BY ADDING SUFFIX CODE "F" AFTER THE RESISTANCE CODE.

\*\*NON-STANDARD VALUES AVAILABLE, WITHIN RESISTANCE RANGE.

## Popular Resistance Values (104 Circuit)\*\*

Resistance			
(Ohms)		Code	
R <sub>1</sub>	R <sub>2</sub>	R <sub>1</sub>	R <sub>2</sub>
160	240	161	241
180	390	181	391
220	270	221	271
220	330	221	331
330	390	331	391
330	470	331	471
3,000	6,200	302	622